



Radiator Oil Emulsifier

An innovative blend of highly effective chemicals to enable the flushing of emulsified oil caused by head gasket failure from all types of cooling systems



Part N°: 84666 - Radiator Oil Emulsifier 250ml

Features

- Suitable for use in all cooling systems
- Fast acting
- Contains powerful additives
- Cleans entire cooling system in one application

Benefits

- Time saving
- Improves cooling system efficiency
- Destroys all emulsified oils
- Reduces risk of overheating

Instructions for use

1. Set Heater controls to "Hot"
 2. Ensure radiator drain plug is free if no drain plug is fitted ensuring bottom hose clip is serviceable.
 3. Start engine and run until normal running temperature is achieved then switch off engine.
 4. Adjust the coolant level to accommodate 250ml of product avoiding discharge through the overflow.
 5. Add product through the water filler cap
 6. Restart engine and allow to run for five minutes
- Switch off engine remove drain plug or bottom hose taking care to avoid contact with hot coolant draining all the coolant immediately into a suitable receptacle.

For larger cooling systems (100L or more)

1. A 250ml bottle of oil emulsifier will pick up its own weight in water and oil. The number of bottles used is dependent on the capacity of the cooling system and the amount of oil in the system. Bring engine up to temp, add 2 bottles, run for 5 mins, and switch off.
2. Check (carefully) if contents of radiator are opaque/milky, if within 10 seconds oil appears on the surface then another treatment is required.
3. Repeat process, either by adding another bottle or 2 to the cooling system or drain the system and add 2 bottles, then repeat. This step may be dependent on where the drain cock is and the safety aspect of the process.
4. For the best results we recommend that the cooling system is treated with 2 bottles and flushed through then repeat process with another 2 bottles.



Technical Information

Part number;	84666
Colour:	Straw coloured
Consistency:	Low viscosity liquid
Density:	0.82g/cm ³
Miscibility water:	miscible
VOC:	764g/l
SDS:	YES
Shelf life:	18 months
Selling unit:	Each
Customs tariff code:	34029090
Volume:	250ml bottle



SDS available on www.kenturope.com

Terms and Conditions

No part of this publication may be reproduced, transmitted or stored, electronically, mechanically or photocopied without the prior permission of KENT (United Kingdom) Ltd. This data sheet and its contents (the "Information") belong to the KENT (United Kingdom) Ltd or are licensed to it. No license is granted for the use of it other than for information purposes in connection with the products to which it relates. No license of any intellectual property rights is granted.

The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error from or omission in it nor for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including

liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence KENT is the trading name of KENT (United Kingdom) Ltd

Registered Office: Amber House, Showground Road, Bridgewater, Somerset, United Kingdom, TA6 6AJ
All rights reserved.

KENT (United Kingdom) Ltd, Forsyth House, Pitreavie Drive, Pitreavie Business Park, Dunfermline, Fife, KY11 8US
Tel : 0800 136925 or 01383 723344 between 08:30-17:30 Monday-Thursday, 09:00-15:00 on Fridays.
For out of hours queries please **Fax** us on 01383 735829 or **Email:** kentinfo.uk@kenturope.com

Rev: 9/3/2017